NASA Technical Memorandum 104742

1N-54 48104 P. 15

Display Format, Highlight Validity, and Highlight Method: Their Effects on Search Performance

Kimberly A. Donner, Tim McKay, Kevin M. O'Brien, and Marianne Rudisill

(NASA-TM-104742) DISPLAY FORMAT, HIGHLIGHT VALIDITY, AND HIGHLIGHT METHOD: THEIR EFFECTS ON SEARCH PERFORMANCE (NASA) 15 P CSCL 05H

N92-10287

Unclas G3/54 0048104

October 1991



√ ~

.

-

Display Format, Highlight Validity, and Highlight Method: Their Effects on Search Performance

Kimberly A. Donner, Tim McKay, and Kevin M. O'Brien Lockheed Engineering & Services Company Houston, Texas

Marianne Rudisill Lyndon B. Johnson Space Center Houston, Texas

National Aeronautics and Space Administration Lyndon B. Johnson Space Center Houston, Texas

October 1991

٣.

CONTENTS

	Page
EXECUTIVE SUMMARY	1
1.0 INTRODUCTION	3
1.0 INTRODUCTION	5
2.0 METHOD	5
2.1 Subjects	E
2.2 Stimulus Display	
2.3 Experimental Design	5
2 4 Procedure	b
3.0 RESULTS	9
3.1 Analysis of the Factorial Design	9
3.2 Analysis of the Highlighting Methods	9
3.3 Observed and Predicted Search Time Performance	10
4.0 DISCUSSION	11
5.0 REFERENCES	11
5.0 REFERENCES	

LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
1.	Examples of the current and reformatted Relative Navigation experimental displays.	6
2.	Examples of the current and reformatted Orbit Maneuver Execute experimental displays.	7
3.	Mean response time as a function of highlight validity and display format.	10

EXECUTIVE SUMMARY

Display format and highlight validity studies (Tullis, 1984; Fisher and Tan, 1989) have shown that these factors affect visual display search performance; however, these studies have been conducted on small, artificial displays of alphanumeric stimuli. A study manipulating these variables was conducted using realistic, complex Space Shuttle information displays. A 2 (display type: Orbit Maneuver Execute, Relative Navigation) x 2 (display format: current, reformatted [following human-computer interface design principles]) x 3 (highlighting validity: valid, invalid, no-highlight) within-subjects analysis of variance found significant main effects of these variables on search time. Search times were faster for items in reformatted displays compared to current displays. Responses to valid applications of highlight were significantly faster than responses to non-highlighted or invalidly-highlighted applications. The significant format by highlight validity interaction showed that there was little difference in response time to both current and reformatted displays when the highlight was validly applied; however, under the no-highlight and the invalid highlight conditions, search times were faster with reformatted displays.

A separate analysis studied the interaction between display format, highlight validity, and several highlight methods. The 2 (display format: current, reformatted) x 2 (highlighting validity: valid, invalid) x 4 (highlight method: brightness, color, flashing, reverse video) within-subjects analysis of variance did not reveal a main effect of highlight method.

In addition, observed display search times were compared to search times predicted by Tullis' Display Analysis Program (1986). Significant correlations between predicted and observed search times were found, although the relationship was highest with non-highlighted displays (\underline{r} = .75) and was less predictive with valid (\underline{r} = -.52) and invalid (\underline{r} = .31) applications of highlight. Issues discussed include the benefits of highlighting and reformatting displays to enhance search, and the necessity to consider both highlight validity and format characteristics in tandem when predicting user search performance.

2.30

1.0 INTRODUCTION

Much research has examined factors which optimize operator search and selection of information from alphanumeric computer displays. Two particular issues have dominated this research in recent years: the effect of format characteristics on search performance has been the focus of work conducted by Tullis (1981, 1983, 1984), and the demonstration of search performance under different levels of highlighting validity has been addressed by Fisher, Coury, Tengs, and Duffy (1989), Fisher and Tan (1989), Tan and Fisher (1987), and Warner, Juola, and Koshino (in press). In Tullis' dissertation (1984), four format characteristics (overall display density, local density, number of groups, and average visual angle of groups) were significant predictors of the time needed to search for a single item of information in a display. Fisher and Tan (1989) found differences in highlight benefit under different levels of highlight validity: when highlight validity was less than 50%, performance with highlighted displays did not differ from performance with displays on which no highlight was present.

In a comparison of format and highlight as predictors of search performance, format can be viewed as the more basic of the two variables. The format of an information display is generally fixed: no changes are made to the overall layout of the information after the display has been implemented. It is at this point that highlight may be applied in order to increase target search and detection. In this sense, highlight may become a subsequent, "quick-fix" solution for poor display design.

However, some research has sought to identify format characteristics that influence search, thereby circumventing the need to apply highlight techniques. Characteristics included in this group are such display format variables as item alignment (Streveler & Wasserman, 1984), and display loading (defined as the percentage of active area on a screen) and grouping (Danchak, 1976).

Recently, much of the interest in format has been concentrated on the variables studied by Tullis (1984). Tullis initially proposed six display format characteristics as possible predictors of search time:

- 1) overall density- percentage of the total number of character spaces available on the display devoted to actual display characters;
- 2) local density- a weighted measure of how close characters were to each other within a 5-degree visual angle;
 - 3) number of groups- a simple count of the number of groups on the display;
- 4) average visual angle of groups- a weighted average (based on the number of characters in a group) of the angles subtended by the groups of information on the display;
- 5) number of items- a simple count of the number of character items present on the display;
- 6) layout complexity- a measure of information alignment (vertical and horizontal complexity measures, based on information theory, are summed to provide a total measure of layout complexity).

Tullis' model was derived via a "regression by leaps and bounds" multiple regression, which provides the best-fitting regression model for each number of predictor variables. Tullis found that each of these search time regression models included at least one of the two grouping variables (i.e., number of groups or average visual angle of groups). The overall 6-predictor model accounted for 50.8% of the variance in his subjects' response times.

Tullis selected the 4-variable model (containing overall density, local density, number of groups, and size of groups), accounting for 48.8% of the variance, as the best model, since the variables in the 5-variable (adding the number of items variable) and 6-variable models did not add significantly to the prediction. This regression model forms the basis for Tullis' Display

Analysis Program (1986). This program evaluates the usability of alphanumeric computer displays, as defined by user search time, by providing a prediction of search time based on measures of these four predictors.

The present study, in part, provides the opportunity to determine how well the Tullis model predicts actual search time for more complex displays of information. Contrasting the response times from the present study and the predicted values from the model provides a measure of the extent to which the Tullis regression model predicts actual search performance. It must be noted that a difference between Tullis-predicted and observed response times could be relative (Tullis, 1986). Tullis has addressed this possibility: "the predicted search times . . . should be viewed as relative rather than absolute measures . . . " (p. 11). He has noted, "... although they [predicted response times] generally have correlated well with empirical data in the literature, the absolute values of the predictions have commonly been wrong . . . specifically, the predicted search times have often been too low" (pp. 11-12).

For example, a significant correlation would imply that poorly-designed displays had longer predicted search times, as found by both the Tullis predictions and the observed data. In this case, the Tullis assertion of predicted search times as relative would be supported.

Recent research has focused on highlighting as a potential method for enhancing visual display search performance. Highlighting is an obvious choice as an influence on the visual search of a display for two reasons: (a) color coding, as one example of a highlight application, has been demonstrated to be effective when searching for a target in an array (Christ, 1975), and (b) the widespread application of highlighting techniques in visual displays with little empirical research prompts an investigation of the implications of highlight use.

The possibility that highlight will be applied to a non-target display item is one such implication. In this event, the attention-attracting quality of highlight may actually be a hindrance to the search process. Research conducted by Fisher and Tan (1989) focused on the consideration that inappropriate application of color to a non-target item may increase search time to the target item. In their work, target search performance was found to be superior on those trials where the target was highlighted when compared to performance when a distractor was highlighted.

Both the validity and the format studies mentioned here have been conducted on displays containing small sets of stimuli. The present study investigated the impact of highlighting on display search performance with actual, complex alphanumeric information displays.

In the present study, highlight, format of the information display, and information display type were manipulated. It was predicted, based on the work of Fisher and Tan (1989), that compared to non-highlighted displays, valid highlighting would result in increased search performance and invalid highlighting would result in a decrease in performance. Performance was predicted to be better under display formats which followed good human factors practices than under the current display formats. An interaction between highlight validity and display format was predicted: It was hypothesized that performance under both display formats would be benefitted by highlight, but that there would be less benefit to highlighting reformance, but were tested in order to provide a greater range of displays.

2.0 METHOD

2.1 Subjects

Twelve Lockheed Engineering and Sciences Company (LESC) employees voluntarily participated in the experiment. All subjects had normal or corrected-to-normal vision, and were unfamiliar with the experimental displays.

2.2 Stimulus Displays

Two current Space Shuttle displays, Orbit Maneuver Execute and Relative Navigation, were presented on an IBM PC/XT with a 13-inch color monitor. These alphanumeric displays were roughly similar in appearance, but they contained information particular to either the Orbit Maneuver Execute or the Relative Navigation task. Regardless of condition, the information occupied almost the entire display area of the monitor. The displays were identical to those used in Burns, Warren, and Rudisill (1985).

Each display type was presented under two kinds of format: current and reformatted. Format changes to improve the current navigation and orbit displays followed good human factors practices (e.g., grouping, alignment of numeric data values) and are enumerated in the Burns et al. paper. Examples of the current and reformatted versions of the navigation and orbit displays are shown in Figures 1 and 2.

Dan Bricklin's Demo II program was used to add highlighting to the displays and to present the stimuli during the study.

2.3 Experimental Design

The experiment followed a 2 x 2 x 3 within-subjects factorial design. The displays presented to each subject varied by combinations of display type (Orbit Maneuver Execute or Relative Navigation), display format (current or reformatted), and highlighting validity (valid, invalid, or no-highlight). Subjects were presented with two replications of each of the different display combinations. Each of the display type by format display combinations was presented twenty times. To avoid order effects, four random sequences of display presentations were used.

Highlight was present on 80% of the displays, equally divided into valid and invalid use of highlight. The highlighted item was either the target item (valid application of highlight) or a randomly-selected distractor display item (invalid application of highlight). The remaining displays (20%) had no highlight and served as a control condition for the use of highlight. When present, the highlight was one of the following techniques: brightness, color (blue), flashing, and reverse video. With the exception of the displays in the blue-highlighted condition, all displays were monochrome.

As in the Tullis (1984) experiment, the dependent measure in this experiment was time needed to supply an answer to a randomly-selected question concerning information contained in the display.

```
2011/033/
                    REL NAV
                                        1 002/22:48:35
                                           000/00:01:39
  RNDZ NAV ENA 1º SV UPDATE
  KU ANT ENA 2* POS 0.76
MEAS ENA 3 VEL 0.96
                                         AVG G ON
                                        €VX
         NAV
                                                  -10.10
                                        ₽VY
                     RR GPC
  SV SEL 4 FLTR
 RNG 49.877 RNG 52.605
R - 5.32 R - 5.90
                                        *VTOT
                                                  479.40
                         5.90
           5.32 R
                                         RESET COMPNT 6
                                                   TOT 7
         358.48 EL
                          + 1.1
 Y
         - 0.24 AZ
                                          SV TRANSFER
            0.0 WP
1:43 WR
                           + 1.0
                                        FLTR MINUS PROP
 NODE 23:11:43
                                         POS 1.55
 FILTER
S TRK 12 RR 13
                                         VEL
                                                     1.02
                                        FLTR TO PROP 8
PROP TO FLTR 9
                        COAS 14*
                  OFFSET X
 STAT
                                        ORB TO TGT
TGT TO ORB
 SLOW RATE
                                                      11
 COVAR REINIT 16
                        MARK HIST
                                           EDIT OVRD
                                         AUT INH FOR
17 18* 19
        RESID RATIO ACPT
                             REJ
        + 1.99
                  0.0
                          0
                                0
         - 0.38
                          0
                  0.0
                                         20
                                              21*
 V/EL/Y -0.05
                  0.1
                                              24*
2011/033/
                     REL NAV 1
                                  MET 002/22:48:35
                                    CDT 000/00:01:39
*RNDZ NAV
                  S VCTR UPDATE
                          0.76
*KU ANT
                   POSTN
                                       #VX
                                               + 36.46
EXT SNSR MSRMT VLCTY
                               0.96
                                            - 10.10
+ 31.74
                                       #VY
*PWRD FLT NAV
                                       €VZ
RESET EV CMPNT
RESET EV TOTAL
                   S VCTR FLTR
                                       EV TOTAL 479.40
                   RNG 49.877
RNG RAT - 5.32
*SLOW RAT
                                       RNDZ RDR GPC
COVAR REINIT
                   <del>0</del>t
                            358.48
                                        RNG 52.605
RNG RAT - 5.90
                            + 0.24
                   Y RAT
                                        EL - 4.6
AZ + 1.1
SENSORS
 S TRK
                   NODE 23:11:43
 RNG RDR
                                        wPITCH + 1.0
* COAS
                  S TRK STATUS
                                        WROLL
S VCTR XFER
                  S TRK OFFSET
 FLTR TO PRPG
PRPG TO FLTR
                   Y
                                         MRK HIST
                                                    EDIT
 ORB TO TGT
TGT TO ORB
                             RSDL RTO ACP RJT
                                                    OVRD
                  RNG + 1.99 0.0
RNG RAT + 0.38 0.0
                                         0
                                               O INHT
 FLTR - PRPG
POSTN 1.55
                                           n
                                                    INHT
                  V/EL/Y - 0.05 0.1
                                          10
```

Figure 1. Examples of the current (top) and reformatted (bottom) Relative Navigation experimental displays.

2.4 Procedure

Subjects performed a computer-generated search and identification task. In each trial, a question concerning one item of Space Shuttle display information was presented (e.g. "What is the value for C1?", "What is the value for node?"). A set of twenty questions was used. The subsequent display contained the information needed to answer the question. Subjects were instructed to signal when they had found the information by pressing the Return key. Response time was defined as the time between information display onset and the press of the Return key. At this point, a response screen appeared and the subject typed the answer value for that question. Subjects received a short break after the first 40 displays. The experiment was self-paced; subjects generally completed the experiment within one hour.

```
ORBIT MNVR EXEC
2021/
                                        1 009/16:52:33
OMS BOTH 1*
                                          000/00:37:31
        L 2
                      BURN ATT
        R 3
                       24 R 336
                                        ■VTOT
                                                   56.7
RCS SEL 4
                       25 P 134
                                        TGO
                                                   3:02
5 TV ROLL 180
                       26 Y 15
TRIM LOAD
                      MNVR 27
                                        VGO X + 43.20
  6 P
      - 1.2
                                              - 7.60
                                            Y
 7 LY + 0.7
                      REI
                                            Z
                                               + 15.40
 8 RY - 1.2
                      TTA
                          15:25
9 WT 209265
                            GMBL
                                             HA
                                                   HP
10 TIG
                           L
                                 R
                                        TGT 147
                                                  +132
   009/17:30:04.8
                        +1.5
                               +2.3
                                        CUR 147
                                                  +129
TGT PEG 4
                        +0.6
                               +1.1
 14 C1
 15 C2
                      PRI 28*
                               29*
                                      35 ABORT TGT
 16 HT
                      SEC 30
OFF 32
                               31
 17 eT
                               33
                                        FWD RCS
 18 PRPLT
                                          ARM
                                              36
TGT PEG 7
                      GMBL CK
                               34
                                          DUMP 37
 19 #VX
              _56.7
                                         OFF 38*
 20 #VY
              0.0
                      EXT #V
                                        SURF DRIVE
             __0.0
 21 #VZ
                                          ON
                                               39
2021/
               ORBIT MNVR EXEC 1
                                    MET 003/00:09:28
                                    IGT 003/00:10:28.0
 SELECT ENGINE
                  BRN ATTITUDE
                                    CDT 000/00:01:00
* BOTH OMS
                   ROLL
                           335
                                    BRN LENGTH 1:33
  LF OMS
                   PITCH
                           179
  RT OMS
                   YAW
                           347
                                    WV TOTAL
                                                   46.5
  RCS
                  SLP/INTRCPT GDC
                                    VELOCITY TO GO
 ENGINE DRIVE
                   Cl
                             2530
                                    Х
                                                 45.70
  PRMRY LF
                           +0.7500
                   C2
                                     ¥
                                                  0.21
  PRMRY RT
                   HT
                         100.500
                                     Z
                                                 47.33
* SCNDY LF
                   eT
                         _78.350
* SCNDY RT
                   PRPNT
                                              CUR
                                                   TGT
                                    APOGEE
                                              130 130
 FWD RCS BRNOFF
                  EXT EV GDC
                                    PERIGEE
                                             +118 +122
  ARM
                   #VX
  DUMP
                   #VY
                                     GIMBAL SETTINGS
                   #VZ
                                              CUR TGT
 LOAD
                                     PTCH LF +0.3 +0.4
                  TRJ VCTR RL 180
 START CDT
                                     PTCH RT +0.5 +0.4
                                    YAW LF -1.4 -1.7
 START MNVR
                  WEIGHT
                           204025
 GIMBAL CHECK
                                     YAW RT +1.8 +1.7
 SURFACE DRIVE
                  RNG TLS
```

Figure 2. Examples of the current (top) and reformatted (bottom) Orbit Maneuver Execute experimental displays.

			•
			•
	•••		
	-		
			•
			7
		·	

3.0 RESULTS

3.1 Analysis of the Factorial Design

(ANOVA) revealed that significant display type differences were present, \underline{F} (1, 132) = 12.09, \underline{p} < .001. Subjects took longer to respond to the navigation displays than to the orbit maneuver displays (mean response time = 17.51 and 13.29 seconds, respectively). The main effect of display format was significant, \underline{F} (1, 132) = 7.22, \underline{p} < .01. Response time to the reformatted displays was significantly shorter (mean = 13.77 seconds) than response time to the current displays (mean = 17.03 seconds). There was a significant difference in the time needed to respond under the three highlight applications, \underline{F} (2, 132) = 22.42, \underline{p} < .0001. As expected, a Student-Newman-Keuls comparison of means showed that mean response time to valid applications of highlight (9.66 seconds) was significantly shorter than mean response time to displays in which no highlighting was present (18.00 seconds) and to invalid applications of highlight (18.54 seconds) at the \underline{p} < .05 level. The difference in response times to no-highlighting displays and displays with invalid application of highlight was not significant.

Display type did not enter into any of the higher-order significant interactions. Among these higher-order interactions, only the format by highlight validity interaction was significant, \underline{F} (2, 132) = 3.62, \underline{p} < .05. For the current displays, a Scheffe test showed a significant difference between valid highlight (mean = 9.04 seconds) and the other highlight validity conditions (\underline{p} < .05). There was no significant difference between no-highlight (mean = 21.20 seconds) and invalid highlight (mean = 20.86 seconds) for current displays (\underline{p} < .05). For the reformatted displays, there was a significant difference between the valid (mean = 10.28 seconds) and invalid (mean = 16.22 seconds) conditions (\underline{p} < .05). The no-highlight condition (mean = 14.81 seconds) did not significantly differ from the other conditions (\underline{p} < .05). The interaction is illustrated in Figure 3.

3.2 Factorial Analysis of the Highlighting Methods

In this section, the difference in response times to several highlight methods was investigated. In order to accomplish this analysis, the no-highlight trials were dropped from the analysis. The data was collapsed across display type for two reasons: (a) the effect of highlight under the different display types was not of interest, and (b) display type did not interact with either the display format or the highlight validity variables in the above factorial. The analysis followed a 2 (display format: current, reformatted) x 2 (highlight validity: valid, invalid) x 4 (highlight method: brightness, color, flashing, reverse video) within-subject design.

The 2 x 2 x 4 ANOVA revealed that the main effect of highlight validity was significant, \underline{F} (1, 176) = 63.53, \underline{p} < .0001, as in the above analysis. Response time to valid highlight (mean = 9.48 seconds) was significantly shorter than response time to invalid highlight (mean = 18.46 seconds). Response time to reformatted displays (mean = 13.09 seconds) was shorter than response time to current displays (mean = 14.85 seconds), but the main effect of display format was not significant, \underline{F} (1, 176) = 2.46, \underline{p} < .12. The main effect of highlight method was not significant, \underline{F} (3, 176) = 1.65, \underline{p} < .18. Response times to the highlight methods were as follows: color (mean = 12.23 seconds), flashing (mean = 13.46 seconds), brightness (mean = 14.60 seconds), and reverse video (mean = 15.59 seconds).

Among the higher-order interactions, only the display format by highlight validity interaction was significant, \underline{F} (1, 176) = 6.93, \underline{p} < .01, similar to the previous analysis.




Figure 3. Mean response time as a function of highlight validity and display format.

3.3 Observed and Predicted Search Time Performance

Of interest in this section was the correlation between the observed display search times and the Tullis-predicted search times. Using Tullis' Display Analysis Program (1986), the experimental displays were evaluated on overall density, local density, number of groups, average visual angle of groups, number of items, and format complexity. The program also provided measures of predicted search time for each experimental display.

The correlation between predicted and observed search time varied, depending on the validity or presence of highlight. The correlation between predicted and observed search times for non-highlighted displays was high and significant, $\underline{r}=.75$, $\underline{p}<.0001$. The correlation was lower for displays with valid ($\underline{r}=-.52$) and invalid ($\underline{r}=.31$) applications of highlight, although both sets of correlations were significant at the $\underline{p}<.05$ level.

Although the association between observed and predicted search times was strong, the predicted search time values and the observed values differed in magnitude. The overall Tullispredicted mean search time was 3.4 seconds. This predicted time was similar under all of the highlight validity conditions, since the Tullis model calculated predicted search times without using highlight as a factor. The overall observed search time was much longer (15.4 seconds). As stated in Section 3.1, the mean observed search times for the valid, no-highlight, and invalid highlight conditions were 9.66, 18.00, and 18.54 seconds, respectively.

4.0 DISCUSSION

The present study strengthens the generalization of previous display format and high-light validity findings taken from studies using more artificial, less complex information displays.

The important findings centered around the highlight validity and the display format manipulations. In this study, significantly shorter search times resulted from both an application of highlight on the appropriate item of information and a reformatting of the current displays.

Performance was best when highlight was validly applied to a target item, regardless of the display format. Despite less than optimal display format in some conditions, items were found quickly simply because the subject's attention was drawn to the lone highlighted item on the display. This highlight benefit was not dependent on the method of highlight.

Format became an issue when the highlight was either not present or was invalidly applied. In these situations, the user's task involved search through the display. In both of these conditions, the search was made faster by display redesign.

The impact of display format on search performance in this study offered two interesting findings. A reformatting of the current displays had a significant influence on the speed with which subjects could locate items on a display, with subjects searching the reformatted displays more efficiently than the current displays. A search performance benefit of highlight was only found under the current displays: the addition of highlight did not aid user search more than a re-grouping of display items. The reformatting was based upon general formatting principles such as alignment and grouping.

In addition, this study demonstrated that Tullis' Display Analysis Program predicts actual search performance with complex, as well as simple, displays. This correlation was highest with the non-highlighted displays, and decreased with the application of display highlight. This finding suggests that, in the absence of other factors affecting search (e.g., highlighting), these format characteristics are strong predictors of performance. However, the lower association under highlighted conditions is evidence that format characteristics should be considered together with other search factors when attempting to optimize the prediction of user search performance.

5.0 REFERENCES

- Bricklin, D. (1987). <u>Demo II</u> [Computer program]. Newton Highlands, MA: Software Garden. Burns, M. J., Warren, D. L., & Rudisill, M. (December, 1985). <u>Expert and nonexpert search task performance with current and reformatted Space Shuttle displays</u> (NASA-JSC Report No. 20967). Houston, TX: Johnson Space Center, Man-Systems Division.
- Christ, R. E. (1975). Review and analysis of color coding research for visual displays. <u>Human Factors</u>, <u>17</u>, 542-570.
- Danchak, M. M. (1976). CRT displays for power plants. <u>Instrumentation Technology</u>, <u>23</u>(10), 29-36.
- Fisher, D. L., Coury, B. G., Tengs, T. O., & Duffy, S. A. (1989). Minimizing the time to search visual displays: The role of highlighting. <u>Human Factors</u>, <u>31</u>, 167-182.
- Fisher, D. L., & Tan, K. C. (1989). Visual displays: The highlighting paradox. <u>Human Factors</u>, 31, 17-30.
- Streveler, D. J., & Wasserman, A. I. (1984). Quantitative measures of the spatial properties of screen designs. <u>Proceedings of the INTERACT '84 Conference on Human-Computer Interaction</u>.

- Tan, K. C., & Fisher, D. L. (1987). Highlighting and search strategy considerations in computer-generated displays. <u>Proceedings of the Human Factors Society 31st Annual Meeting</u> (pp. 524-528). Santa Monica, CA: Human Factors Society.
- Tullis, T. S. (1981). An evaluation of alphanumeric, graphic, and color information displays.

 Human Factors, 23, 541-550.
- Tullis, T. S. (1983). The formatting of alphanumeric displays: A review and analysis. Human Factors, 25, 657-682.
- Tullis, T. S. (1984). Predicting the usability of alphanumeric displays (Doctoral dissertation, Rice University, 1984). <u>Dissertation Abstracts International</u>, <u>45</u>, 1310B.
- Tullis, T. S. (1986). <u>Display Analysis Program. Version 4.0</u> [Computer program and program manual]. Mission Viejo, CA: T. S. Tullis.
- Warner, C. B., Juola, J. F., & Koshino, H. (in press). Voluntary allocation vs. automatic capture of visual attention.

REPORT DOCUMENTATION PAGE			OMB No. 0704-0188		
Public reporting burden for this collection of informat maintaining the data needed, and completing and revinduding suggestions for reducing this burden, to Was 22202-4302, and to the Office of Management and Bud	on is estimated to average 1 hour per response, i	including the time for reviewing instructions, sea ments regarding this burden estimate or any otl formation Operations and Reports, 1215 Jefferso which pot 20503			
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE October 1991	Technical memorandum	NED .		
Their Effects on Search	ght Validity, and Highli n Performance	ight Method:	NDING NUMBERS		
Rudisill	n D. McKay, Kevin M. O'E	Ì	RFORMING ORGANIZATION		
7. PERFORMING ORGANIZATION NAMI Lyndon B. Johnson Spac Houston, Texas 77058	e center	S-	654		
9. SPONSORING/MONITORING AGENC National Aeronautics a Washington, D. C 20	NG Space Mainting of action	1 4/	ONSORING / MONITORING SENCY REPORT NUMBER ASA TM-104742		
11. SUPPLEMENTARY NOTES Donner, McKay, and O'E RudisillJohnson Spa	rienLockheed Engineer ce Center, Crew Station	branch (3/3)	STRIBUTION CODE		
12a DISTRIBUTION/AVAILABILITY STAT UnclassifiedUnlimite Publicly Available Subject Category 54	EMENT ed	126. 01	21KIROLION CODE		
performance; however, alphanumeric stimuli. complex Space Shuttle ance found that searc current displays. Re faster than responses format by highlight v response time to both applied; however, und faster with reformatt display format, highleffect of highlight m search times predicte reformatting displays and format characteri	shlight validity have been these studies have been A study manipulating the information displays. In times were faster for sponses to valid application non- or invalidly healidity interaction show current and reformatted er the non- and invalided displays. A separate ight validity, and seven the second of the contact of the contact of the second of the contact of the contact of the second of the contact of t	nese variable was condu- A 2x2x3 within-subject items in reformatted d ations of highlight wer- ighlighted applications wed that there was litt d displays when the hig- highlight conditions, within-subjects analys ral highlight methods d served display search t alysis Program. Benefit the necessity to consid- dicting search performa	cted using realistic, s analysis of varisplays than for e significantly. The significant le difference in hlight validity was search times were is of variance of id not reveal a main imes were compared to s of highlighting and er highlight validity nce are discussed. 15. NUMBER OF PAGES 14		
Devices		_	16. PRICE CODE 20. LIMITATION OF ABSTRACT		
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	Unlimited		

Form Approved

en de la companya de En la companya de la